

IAP20 Rec'd FCT/PTO 28 MAR 2006

Epilator Apparatus

This invention relates to an epilator apparatus for the removal of hair. The present invention further relates to a method of removing hair by means of an epilator apparatus.

Epilator apparatus are known in the art in a wide variety of embodiments. For example, EP 0 705 546 A2 discloses an epilator having mechanical clamping devices for clamping and plucking hairs. The clamping devices are arranged on an axle and are each comprised of a pair of axially adjacent clamping elements of which at least one of each pair is drivable in axial direction so that the clamping elements of each one pair can be urged against each other axially. In addition, the clamping elements can be driven such as to perform an oscillatory rotary motion. As this occurs, the clamping elements of a pair close while oscillating from a first to a second position to trap a hair, maintaining their closed position while oscillating back into the first position in order to pluck the hair. In particular, each two movable clamping elements are urged against each one stationary clamping element from both sides to avoid undesired vibrations and an attendant noise development.

Furthermore, a rotary cylinder for an epilator apparatus is known from WO 98/05234. The rotary cylinder includes a plurality of pairs of clamping elements essentially arranged in an angularly offset relation to each other. The rotary cylinder further includes actuating elements for bringing the clamping elements into clamping contact with one another in pairs in the area of a plucking zone of the epilator and separating them again subsequently. Moreover, provision is made for at least one control element for controlling the actuating elements. Each pair of clamping elements is assigned a separate, individually movable actuating element.

From U.S. Pat. No. 5,041,122 a depilation apparatus is known which comprises at least one pair of rollers rotating in opposite directions. The roller pair is covered by a shear plate having elongate apertures. The shear plate keeps the skin away from the rollers while enabling the hair to penetrate the apertures in the shear plate to be subsequently caught by the rollers.

The known epilators with discretely plucking clamping devices allow a relatively reliable extraction of the hairs captured by them. However, under marginal conditions

needing to be satisfied for a plucking act as painless as possible and for a lasting effect, the efficiency therewith achievable is not optimal. In the known arrangement with rotary roller pairs for epilation, the process of capturing the hair is a very difficult task so that this system, too, is in need of improvement.

It is an object of the present invention to provide an epilator apparatus that enables an efficient and long-lasting removal of hairs with minimum discomfort for a user.

This object is accomplished with an epilator apparatus embodying the combination of the features of claim 1.

The epilator apparatus of the invention for the removal of hairs is characterized by the provision of a tape which has an adhesive effect and is fed to a plucking zone in which the hairs are plucked from the skin.

The present invention has the advantage that in principle all the hairs can be extracted in the area covered by the tape, because the tape grasps the hairs over its entire surface area, leaving no systematic gaps in the capturing of hairs. The effectiveness thereby achievable is very high.

In a preferred embodiment of the epilator apparatus of the invention, provision is made for a pressure device for applying the tape against the skin, with the tape being desirably oriented relative to the pressure device such as to be applied against the skin with its adhesive side. In this manner reliable adherence of the hairs to the tape is achievable.

In the plucking zone of the epilator apparatus of the invention a deflector device may be arranged which guides the tape away from the skin. As a rule, provision is then made for the tape to be fed from the pressure device to the deflector device. The deflector device may include two juxtaposed deflector elements, with the tape being passed through between the two deflector elements which are preferably urged against each other. In this arrangement it is particularly advantageous for the two deflector elements to be rotatably suspended. With this approach the hairs are extracted from the skin at relatively low speed and essentially perpendicularly to the skin surface while removing a relatively high amount of root together with the hairs. In consequence, the period of time until the epilation act has to be repeated can be extended considerably.

Another advantage resides in that the noise level is relatively low in operation of the epilator apparatus of the invention.

In a preferred embodiment of the epilator apparatus of the invention, the tape can be unwound from a first supply reel. Furthermore, a take-up reel can be provided for receiving the tape. This has the advantage of enabling the tape to be replaced readily and of ensuring a consistent quality of epilation since the tape is used just once. In particular it is also possible for a drive motor to be provided for driving the take-up reel.

Preferably, in the epilator apparatus of the invention provision is made for an additional tape that is caused to converge with the tape in the plucking zone. This has the advantage of binding extracted hairs and ablated scales between the tape and the additional tape and thereby preventing soiling of the epilator apparatus of the invention, so that with the epilator apparatus of the invention a hygienic epilating action can take place without involving elaborate cleaning work. The tape and/or the additional tape may be an adhesive tape. Since adhesive tape is available in an enormous variety and at low cost, it poses no problem providing an adhesive tape with an adhesion suited for the use according to the invention.

Comfortable and reliable operation of the epilator apparatus of the invention can be ensured by providing a device for activating the drive motor when the epilator apparatus is applied against the skin.

The method of the invention for the removal of hair by means of an epilator apparatus is characterized in that a tape is brought into contacting relation to the skin by the epilator apparatus, whereby the hairs adhere to the tape, the tape is fed to a plucking zone of the epilator apparatus, and the hairs are plucked from the skin in the plucking zone.

In particular, the method of the invention is designed to comprise guiding the tape away from the skin in the plucking zone and thereby lifting the hairs relative to the skin. In this manner the hairs are reliably grasped for the plucking action. Together with the tape, the lifted hairs can be held clamped between two deflector elements and extracted from the skin. In this method it is particularly advantageous for the tape to set the two deflector elements in rotary motion of opposite direction. During epilation,

the surrounding skin can be held fixed by the deflector elements. Preferably, the method of the invention is designed to keep the hairs adhered to the tape after plucking and to carry them away together with the tape.

The movements necessary for epilation may be generated in a variety of ways. For example, the possibility exists for the feeding movement of the tape to produce a forward movement of the epilator apparatus relative to the skin. Alternatively, it is also possible to drive the tape by manually advancing the epilator apparatus relative to the skin.

The present invention will be explained in more detail in the following with reference to the embodiment illustrated in the accompanying drawing.

The sole Figure of the drawing is a highly schematic sectional view of an embodiment of an epilator apparatus 1 constructed in accordance with the invention. The epilator apparatus 1 is shown during the act of epilating involving the removal of hairs 3 from the skin 2. The epilator apparatus 1 includes an adhesive tape 5 wound on a first supply reel 4 and fed to a take-up reel 8 via a pressure roller 6 and a first guide roller 7. Further provided is a second supply reel 9 holding an additional adhesive tape 10 which is fed to the take-up reel 8 via a second guide roller 11. In addition, the epilator apparatus 1 has a casing 12. The first supply reel 4, the take-up reel 8 and the second supply reel 9 may be arranged at nearly any position in or on the epilator apparatus 1. In this context, however, attention has to be paid to ensure that the adhesive tape 5 and the additional adhesive tape 10 can be guided in the above-described manner. If necessary, the adhesive tape 5 and/or the additional adhesive tape 10 may be guided through further rollers not shown in the Figure. The pressure roller 6 and the two guide rollers 7 and 11 are arranged on that end of the epilator apparatus 1 that is applied against the skin 2 during epilation. At this end the casing 12 is open toward the skin 2, so that the pressure roller 6 and the two guide rollers 7 and 11 are accessible from outside. The pressure roller 6 urges the adhesive tape 5 against the skin 2, with the adhesive side of the tape 5 resting against the skin 2. Furthermore, the adhesive tape 5 is oriented parallel to the surface of the skin 2 by the pressure roller 6 in cooperation with the first guide roller 7. The first guide roller 7 and the second guide roller 11 are located in close proximity to one another in a plucking zone in which the hairs 3 are plucked from the skin 2. The adhesive tape 5 and the additional adhesive tape 10 are

passed between the two guide rollers 7 and 11, with their adhesive sides being pressed against each other for adhesive bonding. In this condition, the adhesive tape 5 and the additional adhesive tape 10 are wound onto the take-up reel 8 jointly. The winding-up process is assisted by a drive motor not shown in the Figure, which sets the take-up reel 8 in rotation. The direction of rotation of the take-up reel 8 is shown by an arrow. Equally, the directions of rotation of the supply reels 4 and 9, the directions of feed of the adhesive tape 5 and the additional adhesive tape 10 as well as the direction of movement of the epilator apparatus 1 are also shown by arrows.

With the epilator apparatus 1 of the invention the act of hair removing is performed in the following manner:

As shown in the Figure, the epilator apparatus 1 is placed against the skin 2 such that the adhesive sides of the adhesive tape 5 and of the additional adhesive tape 10 are urged into contacting relation to the skin by the pressure roller 6 and the first guide roller 7 and, respectively, the second guide roller 11. As the epilator apparatus 1 is applied against the skin 2, the drive motor of the take-up reel 8 is activated, setting the take-up reel 8 in rotation. The drive motor is activated by a sensor arrangement using, for example, a pressure-operated switch. The rotational velocity of the take-up reel 8 can be predetermined via a control of the drive motor. Rotation of the take-up reel 8 causes the adhesive tape 5 and the additional adhesive tape 10 to be wound onto the take-up reel 8 in adhesive-bonded condition. Correspondingly, the adhesive tape 5 and the additional adhesive tape 10 are unwound from their supply reels 4 and 9. The adhesive tape 5 fed from the first supply reel 4 to the take-up reel 8 is applied against the skin 2 by the pressure roller 6. As a result of the adhesive effect produced by the adhesive tape 5 on the skin 2 and the hairs 3, the epilator apparatus 1 is moved parallel to the surface of the skin 2 at a velocity v amounting to the feed rate of the adhesive tape 5. In the representation shown in the Figure, the epilator apparatus 1 moves from right to left. As this movement proceeds, the adhesive side of the adhesive tape 5 continually makes contact with more hairs 3 then adhering to the adhesive tape 5. On passing the first guide roller 7, the hairs 3 adhering to the adhesive tape 5 are lifted due to the deflection of the adhesive tape 5 and are clamped between the adhesive tape 5 and the additional adhesive tape 10 by the two guide rollers 7 and 11 which are pressed against each other. By reason of the clamping action produced by

the guide rollers 7 and 11 and the adhesive effect between the adhesive tape 5 and the additional adhesive tape 10, the hairs 3 are entrained with the adhesive tape 5 and the additional adhesive tape 10 and plucked out in the process, that is, the skin 2 is epilated.

In the use of guide rollers 7 and 11 of equal size, epilation takes place at an angle of 90° relative to the surface of the skin 2. The velocity at which the hairs 3 are plucked from the skin 2 equals the velocity v of the epilator apparatus 1 or the adhesive tape 5 and is relatively low. The relatively low plucking speed and the vertical orientation of the plucking motion relative to the skin surface have the effect of a relatively high root portion being removed together with the hairs 3. During the process of epilation, the two guide rollers 7 and 11 largely prevent the skin 2 in the immediate vicinity of the hair 3 just extracted from yielding to the pulling tension applied to the skin 2 by this particular hair 3, so that the pain caused by epilation can be kept at a relatively low level. The extracted hairs 3 as well as ablated scales are trapped between the adhesive tape 5 and the additional adhesive tape 10 and carried away to prevent soiling of the epilator apparatus 1. When the adhesive tape 5 and the additional adhesive tape 10 are completely unwound from the supply reels 4 and 9, the supply reels 4 and 9 are replaced. This also includes replacement of the take-up reel 8 holding the adhesive tape 5 adhesive-bonded to the additional adhesive tape 10.

In the above-described embodiment of the epilator apparatus 1 the advancing motion of the epilator apparatus 1 relative to the skin 2 is produced by means of the drive motor for the take-up reel 8. To perform epilation, the user merely applies the epilator apparatus 1 against the skin 2, guiding it manually to determine the direction of the forward movement. Alternatively, the possibility also exists for the epilator apparatus 1 to dispense with a drive motor for the take-up reel 8. In this event, the forward movement of the epilator apparatus 1 is produced manually, thereby driving the tape 5.

In another modification of the epilator apparatus 1, a masking tape having no adhesive coating is substituted for the additional adhesive tape 10. Moreover, it is also possible to dispense with the additional adhesive tape 10 and hence the second supply reel 9 entirely. In this event, the second guide roller 11 may be maintained to enable the hairs 3 to be clamped between the adhesive tape 5 and the second guide roller 11.

Another possibility includes replacing the adhesive tape 5 with a tape which is not coated with an adhesive, producing adherence of the hairs 3 in some other way. Adherence of the hairs 3 could be also accomplished, for example, by providing the tape with a suitable surface structure or charging it electrostatically.

The adhesive tape 5 and, if applicable, also the additional adhesive tape 10 inclusive of the required supply and take-up reels, pressure and guide rollers may be constructed as an assembly or cartridge replaceable as a complete unit. This enables a simple and particularly hygienic disposal of the adhesive tape and the adhering hairs.

In a further aspect of the epilator apparatus 1, devices are provided to influence the orientation of the hairs 3 adhering to the adhesive tape 5. Such devices attempt in particular to align the hairs 3 in the direction of movement of the adhesive tape 5 in order to facilitate lifting of the hairs 3 from the skin 2 in the plucking zone. For alignment of the hairs 3, a comb arranged to precede the pressure roller 6 may be provided, for example. In lieu of the comb, a cylinder may also be used. Of particular advantage is an actively driven comb or a brush, in particular a cylindrical brush, which combs the hairs toward the adhesive tape 5 and aligns the hair ends in this direction. Moreover, the alignment of the hairs 3 may also be influenced by an electrostatic charge. In addition, by suitably selecting the direction of forward movement of the epilator apparatus 1 relative to the orientation of the hairs 3 on the skin 2, the user is also offered the possibility of acting on the alignment of the hairs 3 on the adhesive tape 5.